

F700(VIPER)

New Generation-Videoscope
for Industrial Inspection

- 3.5" TFT LCD
- LED brightness/contrast adjustment
- Zoom in and mirror
- Video record and snapshot
- AV out
- Black/White and color modes (optional)
- Measurement mode (optional)
- SKYPE communications supported (optional)
- 4 X AA batteries for 3 hours operation



LED BRIGHTNESS
ADJUSTMENT



*MIRROR
VIEW



ASF FORMAT;
COMPLIANT WITH
MPEG 4



JPG FORMAT;
640 X 480 PIXEL



UP TO 32G




NTSC/PAL



BLACK AND
WHITE PATTERN



MEASUREMENT SOFTWARE



Specifications	
System Dimension	275mm*123mm*55mm
System Weight	370g (w/o batteries)
Display	3.5" TFT LCD QVGA
Power	4 X AA 1.5V batteries (included)
Recording Medium	SD CARD (supports up to 32G)
Video Out Fomats	NTSC & PAL /AV out
Video/Photo Resolution	640 X 480 pixels (VGA)
Video/photo File Fomat	.avi;.jpg
Video Playback Speeds	12 % ,25 % ,50 % ,1x,1.5x,2x,4x

Insert Tube Options:

- **FRONT / SIDE VIEW PROBE:** 3.9mm,5.5mm
- **DUAL CAMERA PROBE:** 4.9mm
- **TWO WAY ARTICULATION:** 6.0mm
- **HYPERION PROBE:** 5.5mm,6.0mm

